

VISION200™

Advanced PLCs with an integrated operator panel graphic or touch. Snap-in I/Os to create an All-in-One; expand up to 316 I/Os

Features:

HMI

- Up to 255 user-designed screens
- Hundreds of images per application
- HMI graphs & Trends
- Virtual alpha-numeric keypad (in V290 & V530)
- Memory and communication monitoring via HMI - No PC needed

PLC

- I/O options include high-speed, temperature & weight measurement
- Auto-tune PID, up to 12 independent loops
- Recipe programs and datalogging via Data Tables
- Date & Time-based control

Communication

- TCP/IP via Ethernet
- Send e-mail function
- SMS messaging
- GPRS/GSM
- Remote Access utilities
- MODBUS protocol support
- CANbus: CANopen, UniCAN, CANlayer 2
- FB Protocol Utility: enables serial or TCP/IP communications with 3rd-party device; barcode readers, frequency converters, etc
- Ports: supplied with 1 RS232, 1 RS232/RS485 and 1 CANbus; 1 port may be added for serial/Ethernet
- V280-B25B & V290-B25B Not yet UL certified.

	V230™	V260™	V280™	V290™	V530™
Article Number	V230-13-B20B	V260-16-B20B	V280-18-B20B	V290-19-B20B	V530-53-B20B
I/O Options	Snap-in I/O Modules Plug these modules directly into the back of the Vision unit to create a self-contained PLC with up to 62 I/Os. Inputs may include Digital, Analog and Temperature Measurement. Outputs may include Transistor, Relay or Analog (sold separately)				
I/O Expansion	Local or remote I/Os may be added via expansion port or via CANbus				
Program	Application Memory				
	1MB				
Scan Time	30µsec per 1K of typical application				
Operands	4096 coils, 2048 registers, 256 long integers (32 bit), 64 double words (32 bit unsigned), 24 memory floats, 192 timers, 24 counters				
Data Tables	120K dynamic RAM data (recipe parameters, datalogs, etc.), up to 256K fixed data				
Operator Panel	Type				
	STN LCD	Negative blue, STN LCD	Black & White FSTN LCD		
Display Resolution & Size	128 x 64 pixels 3.2"	240 x 64 pixels 5.4"	320 x 240 pixels (QVGA), 4.7" active area	320 x 240 pixels (QVGA), 5.7" active area	
Touch Screen	None	None	Resistive, Analog		
Keys	24 user labeled keys	33 user labeled keys	27 user labeled keys	Virtual keyboard	
General	Power Supply				
	12/24VDC				
Battery Back-up	7 years typical at 25°C, back-up for all memory sections and real-time clock (RTC)				
Environment	IP65/NEMA4X (when panel mounted)				
Standard	CE, UL Many of our products are also UL Class 1 Div 2 and GOST certified - please contact Unitronics				

Vision™ OPLC™

Technical Specifications Models V230/260/280/290

This guide provides specifications for Unitronics' models V230-13-B20B, V260-16-B20B, V280-18-B20B, V290-19-B20B.

You can find additional information on the Unitronics Setup CD and in the Technical Library at www.unitronics.com.

Technical Specifications

Power Supply

Input voltage	12VDC or 24VDC
Permissible range	10.2VDC to 28.8VDC with less than 10% ripple
Max. current consumption	

	V230	V260	V280	V290
@12VDC	280mA	460mA	540mA	470mA
@24VDC	140mA	220mA	270mA	230mA
Typical power consumption	2.5W	4.2W	5.4W	5.1W

Battery

Back-up	7 years typical at 25°C, battery back-up for RTC and system data, including variable data.
Replacement	Yes. Refer to instructions in the document: <i>Replacing a Battery V230-260-280-290.pdf</i> , available from Unitronics' Technical Library.

Graphic Display Screen

	V230	V260	V280	V290
LCD Type	STN	Neg. blue STN	Graphic B&W FSTN	
Illumination backlight	LED yellow-green	CCFL fluorescent lamp		
Display resolution, pixels	128x64	240x64	320x240 (QVGA)	
Viewing area	3.2"	5.4"	4.7"	5.7"
Touchscreen	None		Resistive, analog	
'Touch' indication	None		Software (SB16)	Software (SB16); Via buzzer
Screen contrast	Manually adjusted. Refer to VisiLogic Help topic: <i>Setting LCD Contrast/Brightness</i>		Via software (Store value to SI 7). Refer to VisiLogic Help topic: <i>Setting LCD Contrast/Brightness</i>	

Keyboard

	V230	V260	V280	V290
Number of keys	24	33	27	none (virtual)
	Includes soft keys and alphanumeric keypad			
Key type	Metal dome, sealed membrane switch			none
Slides	Picture, alphanumeric keypad, and Function keys			none

Program

Application memory	1MB		
Operand type	Quantity	Symbol	Value
Memory Bits	4096	MB	Bit (coil)
Memory Integers	2048	MI	16-bit signed/unsigned
Long Integers	256	ML	32-bit signed/unsigned
Double Word	64	DW	32-bit unsigned
Memory Floats	24	MF	32-bit signed/unsigned
Timers	192	T	32-bit
Counters	24	C	16-bit
Data Tables	120K (dynamic)/192K (static)		
HMI Displays	Up to 255		
Scan Time	30µsec per 1K of typical application		

Communication

Serial Ports	2. See Note 1		
RS232			
Galvanic isolation	No		
Voltage limits	±20V absolute maximum		
Baud rate range	COM1	COM2	
	300 to 57600 bps	300 to 115200 bps	
Cable length	Up to 15m (50')		
RS485			
Galvanic isolation	No		
Voltage limits	-7 to +12V differential maximum		
Baud rates	300 to 115200 bps		
Nodes	Up to 32		
Cable type	Shielded twisted pair, in compliance with EIA RS485		
Cable length	Up to 1200m (4000')		
CANbus port	1		
Nodes	CANopen	Unitronics' CANbus protocols	
	127	60	
Power requirements	24VDC (±4%), 40mA max. per unit		
Galvanic isolation	Yes, between CANbus and controller		
Cable length/ baud rate	25 m	1 Mbit/s	
	100 m	500 Kbit/s	
	250 m	250 Kbit/s	
	500 m	125 Kbit/s	
	500 m	100 Kbit/s	
	1000 m*	50 Kbit/s	* If you require cable lengths over 500 meters, contact technical support.
	1000 m*	20 Kbit/s	
Optional port	User may install an additional port, available by separate order. Available port types are: RS232/RS485, and Ethernet.		

Notes:

1. COM1 supports RS232 only.
COM2 may be set to either RS232/RS485 according to jumper settings as shown in the product's Installation Guide. Factory setting: RS232.

I/Os

Via module	Number of I/Os and types vary according to module. Supports up to 256 digital, high-speed, and analog I/Os.
Snap-in I/O modules	Plugs into rear port to create self-contained PLC with up to 43 I/Os.
Expansion modules	Local adapter, via I/O Expansion Port. Integrate up to 8 I/O Expansion Modules comprising up to 128 additional I/Os. Remote I/O adapter, via CANbus port. Connect up to 60 adapters; connect up to 8 I/O expansion modules to each adapter.

Dimensions

Size	See mechanical drawings in the document <i>V230_260_280_290 Installation Guide.pdf</i> , available from Unitronics' Technical Library.			
	V230	V260	V280	V290
Weight	429g (15.1 oz)	695g (24.5 oz)	860g (30.4 oz)	840g (29.7 oz)

Mounting

Panel-mounting	Via brackets
----------------	--------------

Environment

Inside cabinet	IP20 / NEMA1 (case)
Panel mounted	IP65 / NEMA4X (front panel)
Operational temperature	0 to 50°C (32 to 122°F)
Storage temperature	-20 to 60°C (-4 to 140°F)
Relative Humidity (RH)	5% to 95% (non-condensing)

The information in this document reflects products at the date of printing. Unitronics reserves the right, subject to all applicable laws, at any time, at its sole discretion, and without notice, to discontinue or change the features, designs, materials and other specifications of its products, and to either permanently or temporarily withdraw any of the foregoing from the market.

All information in this document is provided "as is" without warranty of any kind, either expressed or implied, including but not limited to any implied warranties of merchantability, fitness for a particular purpose, or non-infringement. Unitronics assumes no responsibility for errors or omissions in the information presented in this document. In no event shall Unitronics be liable for any special, incidental, indirect or consequential damages of any kind, or any damages whatsoever arising out of or in connection with the use or performance of this information.

The tradenames, trademarks, logos and service marks presented in this document, including their design, are the property of Unitronics (1989) (R"G) Ltd. or other third parties and you are not permitted to use them without the prior written consent of Unitronics or such third party as may own them.

DTS-V2xx 06/08